

OEG LED Floodlight for construction sites

Art. No. 311 778 260

Technical data:

Power supply:	230 V~ via power cable
Output:	50 W
Colour temperature:	6,000 K
Light output:	3,700 lm
Type of protection:	IP65

Scope of delivery:

LED floodlight, power cable,
foot with screws, operating instructions

As part of our ongoing product development, specifications of the product may change.

Safety notes:

When the work light is in use, please observe the following:

- Do not look directly into the floodlight.
- Do not direct into a person's or an animal's eyes.
- Do not point the beam at vehicles or machines that are operated by a person.
Bright light can be blinding and you could cause a serious accident.

Assembly of the tool:

- Unpack the floodlight carefully and check for damages. Please make sure that all parts of the device are present and in perfect condition. If any parts are missing or damaged, have them replaced before you use the floodlight.
- Fasten the floodlight on the foot by means of the knurled screws enclosed. The work light is ready for operation now.
Alternatively, the floodlight may also be mounted to any other surface. Use the existing bore holes at the mounting bracket.

Use of the LED floodlight:

- The floodlight is on, as soon as it has been connected with the power supply. The device is turned on and off by simply inserting the plug or removing it from the mains socket.
- The floodlight complies with IP65. It is protected against ingress of dust and splashing water.
It is suitable for indoor as well as outdoor use.

Maintenance and cleaning:

- Use a damp cloth with a mild detergent for cleaning.
- There are no serviceable parts inside the floodlight.

Disposal:

- Always adhere to national regulations when disposing of power tools.
- Do not dispose of the floodlight together with your household waste.
- Contact your local disposal authority for information on the correct way how and where to dispose of electric devices.

