



This buffer storage tank fulfills the highest demands on heat storage. Due to its highly efficient insulation, the heat-retaining loss is significantly reduced compared to common storage tanks. The purpose of the buffer storage tank is to balance the difference between generated heat and consumed heat. So the heat generators can be operated more independently from the consumption.

Data pursuant to EU regulation 812/2013

Name of supplier's trade marks:	OEG GmbH
Model identification of the supplier:	516005299 - OEG buffer storage tank 300 l
Energy efficiency class of the model:	A+
Heat retaining losses in watts:	36
Storage tank volume in litres:	298

General

OEG Nr.:	516005299
Rated volume according to EN 12897:	300
Colour:	silver
Insulation according to DIN 4102-1 Fire Protection Class B2:	solid foamed insulation
Weight [kg]:	71
Total height including insulation [mm]:	1750
Diameter with insulation [mm]:	610
Tilt height [mm]:	1830

Energy

Energy efficiency class according to EU regulation no. 812/2013:	A+
Heat retaining loss according to EN 12897 [W]:	36
Heat losses in stand-by mode according to DIN 12897 [kW/h / 24 h]:	0,864



Tank	
Real volume according to EN 12897 [l]:	298
p _{max} Tank [bar]:	3
t _{max} Tank [°C]:	95
t _{min} Tank [°C]:	20

Connections	
Connection layout:	180°
Connection sensor [Ø mm / terminal]:	6 mm
Connection heat generator [thread]:	R 1"
Connection heating element [thread]:	Rp 1 1/2"
Max. immersion depth of screw-in heater [mm]:	500