


OEG Solar storage tank 3Plus 300 l with 3 smooth-pipe heat exchangers



OEG Solar storage tanks - highest quality "Made in Germany"!

The OEG solar storage tank 3Plus is suitable not only for heating up domestic water with boilers and low-temperature heating systems but particularly for the additional connection of a solar system.

The third smooth-pipe heat exchanger can be perfectly used for a return flow boost.

The storage tank is used as a new installation but also very often as a replacement tank. Thanks to the wide range of selectable coating colours and the various connection options, a combination with heat generators and solar systems of almost any manufacturer is possible.

The inner surface of the storage tank is coated with high-quality enamel to ensure the hygienic heating of drinking water. The generously-dimensioned heat exchanger surface of the lower smooth-pipe heat exchanger reaches down to the bottom of the tank, and thus provides a huge energetic advantage compared to many other products in the market.

The service hatch allows for convenient maintenance and cleaning of the tank.

Data pursuant to EU regulation 812/2013

| | |
|---------------------------------------|---|
| Name of supplier's trade marks: | OEG GmbH |
| Model identification of the supplier: | 516005172 - Solar storage tank 3Plus 300 l with 3 smooth-pipe heat exchangers |
| Energy efficiency class of the model: | A+ |
| Heat retaining losses in watts: | 35 |
| Storage tank volume in litres: | 290 |

General

| | |
|--|-------------------------|
| OEG Nr.: | 516005172 |
| Rated volume according to EN 12897: | 300 |
| Colour: | blue |
| Insulation according to DIN 4102-1 Fire Protection Class B2: | solid foamed insulation |
| Weight [kg]: | 134 |
| Total height including insulation [mm]: | 1750 |
| Diameter with insulation [mm]: | 610 |
| Tilt height [mm]: | 1830 |

Energy

| | |
|--|-------|
| Energy efficiency class according to EU regulation no. 812/2013: | A+ |
| Heat retaining loss according to EN 12897 [W]: | 35 |
| Heat losses in stand-by mode according to DIN 12897 [kW/h / 24 h]: | 0,840 |
| Output capacity (45°C) [l]: | 471 |
| Performance indicator NL following DIN 4708: | 10 |

OEG Solar storage tank 3Plus 300 l with 3 smooth-pipe heat exchangers



Tank

| | |
|--|-----|
| Real volume according to EN 12897 [l]: | 290 |
| p _{max} Tank [bar]: | 10 |
| t _{max} Tank [°C]: | 95 |
| t _{min} Tank [°C]: | 20 |

Smooth-pipe heat exchanger

| | |
|--|------|
| Smooth-pipe heat exchanger [number]: | 3 |
| Smooth-pipe heat exchanger area bottom [m²]: | 1,15 |
| Smooth-pipe heat exchanger surface middle [m²]: | 1,15 |
| Smooth-pipe heat exchanger area top [m²]: | 0,77 |
| Smooth-pipe heat exchanger volume bottom: | 7,50 |
| Smooth-pipe heat exchanger volume middle: | 7,50 |
| Smooth-pipe heat exchanger volume top: | 5,05 |
| p _{max} Smooth-pipe heat exchanger [bar]: | 10 |
| t _{max} Smooth-pipe heat exchanger [°C]: | 130 |

Connections

| | |
|---|-----------|
| Connection layout: | 180° |
| Connection sensor [Ø mm / terminal]: | 6 mm |
| Connection cold / hot water: | R 1" |
| Connection heat exchanger [thread]: | Rp 1" |
| Connection circulation: | R 3/4" |
| Connection heating element [thread]: | Rp 1 1/2" |
| Service hatch (LK 150): | 115 / 180 |
| Max. immersion depth of flange heater [mm]: | 420 |
| Max. immersion depth of screw-in heater [mm]: | 500 |