

OEG Hot water storage tank 200 litres with 1 smooth pipe heat exchanger



Hot-water storage tanks for heating up domestic water by means of boilers and low-temperature systems of all manufacturers. The inner surface of the storage tank is coated with a high-quality enamelling. The generously dimensioned heat exchanger surface that reaches down to the bottom ensures excellent heat transmission. A laterally positioned service hatch makes it possible to maintain and clean the storage tank conveniently, and it can be fitted with an electric heating element if required. The unrivalled OEG vacuum insulation of the storage tanks ensures there are significantly lower heat losses than the insulations of customary storage tanks.

Data pursuant to EU regulation 812/2013

Name of supplier's trade marks:	OEG GmbH
Model identification of the supplier:	516008004 - Hot water storage tank 200 litres with 1 smooth pipe heat exchanger
Energy efficiency class of the model:	A+
Heat retaining losses in watts:	31
Storage tank volume in litres:	201

General

OEG Nr.:	516008004
Rated volume according to EN 12897:	200
Colour:	blue
Insulation according to DIN 4102-1 Fire Protection Class B2:	solid foamed insulation
Weight [kg]:	80
Total height including insulation [mm]:	1265
Diameter with insulation [mm]:	610
Tilt height [mm]:	1375

Energy

Energy efficiency class according to EU regulation no. 812/2013:	A+
Heat retaining loss according to EN 12897 [W]:	31
Heat losses in stand-by mode according to DIN 12897 [kW/h / 24 h]:	0,744
Output capacity (45°C) [l]:	315
Performance indicator NL following DIN 4708:	5

OEG Hot water storage tank 200 litres with 1 smooth pipe heat exchanger



Tank

Real volume according to EN 12897 [l]:	201
p _{max} Tank [bar]:	10
t _{max} Tank [°C]:	95
t _{min} Tank [°C]:	20

Smooth-pipe heat exchanger

Smooth-pipe heat exchanger [number]:	1
Smooth-pipe heat exchanger area bottom [m²]:	1,15
Smooth-pipe heat exchanger volume bottom:	7,50
p _{max} Smooth-pipe heat exchanger [bar]:	10
t _{max} Smooth-pipe heat exchanger [°C]:	130

Connections

Connection layout:	180°
Connection sensor [Ø mm / terminal]:	6 mm
Connection cold / hot water:	R 1"
Connection heat exchanger [thread]:	Rp 1"
Connection circulation:	R 3/4"
Connection heating element [thread]:	Rp 1 1/2"
Service hatch (LK 150):	115 / 180
Max. immersion depth of flange heater [mm]:	420
Max. immersion depth of screw-in heater [mm]:	400