


## Pure+ Fresh-Water storage tank 1,500 litres with 2 smooth pipe heat exchangers



Fresh-water storage tank for highest demands on drinking water hygiene and energy efficiency.

The structure of the storage tank is fundamentally different from usual large-volume domestic hot-water tanks. A built-in corrugated stainless steel pipe separates the drinking water from the heating water, while serving as a powerful heat exchanger at the same time. Thus, the advantages of a buffer tank are combined with those of a continuous flow water heater. The heating water serves as actual heat storage while the drinking water flows through the corrugated stainless steel pipe only if required and, thus, a legionella-safe domestic water heating is ensured. You do not need a protection programme against legionella in the controller. At all times, the consumer is provided with hygienically clean, fresh water at the desired temperature.

Due to the two additional smooth-pipe heat exchangers, more heat generators can be integrated at any time and their energy can be fed into the fresh-water storage tank.

### Data pursuant to EU regulation 814/2013

Name of supplier's trade marks:	OEG GmbH
Model identification of the supplier:	516008138 - Fresh-Water storage tank 1,500 litres with 2 smooth pipe heat exchangers
Heat retaining losses in watts:	63
Storage tank volume in litres:	1464

### General

OEG Nr.:	516008138
Rated volume according to EN 12897:	1500
Colour:	white
Insulation according to DIN 4102-1 Fire Protection Class B2:	removable segment insulation
Weight [kg]:	365
Total height including insulation [mm]:	2210
Diameter without insulation [mm]:	1000
Diameter with insulation [mm]:	1315
Tilt height [mm]:	2190

### Energy

Heat retaining loss according to EN 12897 [W]:	63
Heat losses in stand-by mode according to DIN 12897 [kW/h / 24 h]:	1,512
Output capacity (45°C) [l]:	857
Performance indicator NL following DIN 4708:	8,40

# Pure+ Fresh-Water storage tank 1,500 litres with 2 smooth pipe heat exchangers



## Tank

Real volume according to EN 12897 [l]:	1464
p <sub>max</sub> Tank [bar]:	3
t <sub>max</sub> Tank [°C]:	95
t <sub>min</sub> Tank [°C]:	20

## DHW heat exchanger

DHW heat exchanger area [m²]:	8
DHW heat exchanger volume [l]:	34,20
p <sub>max</sub> DHW heat exchanger [bar]:	6
t <sub>max</sub> DHW heat exchanger [°C]:	95

## Smooth-pipe heat exchanger

Smooth-pipe heat exchanger [number]:	2
Smooth-pipe heat exchanger area bottom [m²]:	4,50
Smooth-pipe heat exchanger area top [m²]:	2,80
Smooth-pipe heat exchanger volume bottom:	29,70
Smooth-pipe heat exchanger volume top:	18,60
p <sub>max</sub> Smooth-pipe heat exchanger [bar]:	10
t <sub>max</sub> Smooth-pipe heat exchanger [°C]:	130

## Connections

Connection layout:	90°
Connection sensor [Ø mm / terminal]:	6 mm
Connection cold / hot water:	Rp 1 1/4"
Connection heat generator [thread]:	Rp 1 1/2"
Connection heat exchanger [thread]:	Rp 1"
Connection heating element [thread]:	Rp 1 1/2"
Max. immersion depth of screw-in heater [mm]:	1100