

## Pure+ Fresh-Water storage tank 2,250 litres with 2 smooth pipe heat exchangers



Fresh-water storage tank for highest demands on drinking water hygiene and energy efficiency.

The structure of the storage tank is fundamentally different from usual large-volume domestic hot-water tanks. A built-in corrugated stainless steel pipe separates the drinking water from the heating water, while serving as a powerful heat exchanger at the same time. Thus, the advantages of a buffer tank are combined with those of a continuous flow water heater.

The heating water serves as actual heat storage while the drinking water flows through the corrugated stainless steel pipe only if required and, thus, a legionella-safe domestic water heating is ensured. You do not need a protection programme against legionella in the controller. At all times, the consumer is provided with hygienically clean, fresh water at the desired temperature.

Due to the two additional smooth-pipe heat exchangers, more heat generators can be integrated at any time and their energy can be fed into the fresh-water storage tank.

### General

OEG Nr.:	516008144
Rated volume according to EN 12897:	2250
Colour:	white
Insulation according to DIN 4102-1 Fire Protection Class B2:	removable PES fleece insulation 0.036 W/(mK)
Weight [kg]:	415
Total height including insulation [mm]:	2165
Diameter without insulation [mm]:	1250
Diameter with insulation [mm]:	1450
Tilt height [mm]:	2240

### Energy

Output capacity (45°C) [l]:	1142
Performance indicator NL following DIN 4708:	10

### Tank

$p_{\max}$ Tank [bar]:	3
$t_{\max}$ Tank [°C]:	95
$t_{\min}$ Tank [°C]:	20

### DHW heat exchanger

DHW heat exchanger area [m²]:	9
DHW heat exchanger volume [l]:	39,50
$p_{\max}$ DHW heat exchanger [bar]:	6
$t_{\max}$ DHW heat exchanger [°C]:	95

Pure+ Fresh-Water storage tank 2,250 litres  
with 2 smooth pipe heat exchangers



Smooth-pipe heat exchanger

Smooth-pipe heat exchanger [number]:	2
Smooth-pipe heat exchanger area bottom [m²]:	4,90
Smooth-pipe heat exchanger area top [m²]:	2,50
Smooth-pipe heat exchanger volume bottom:	32
Smooth-pipe heat exchanger volume top:	16
p <sub>max</sub> Smooth-pipe heat exchanger [bar]:	10
t <sub>max</sub> Smooth-pipe heat exchanger [°C]:	130

Connections

Connection layout:	90°
Connection sensor [Ø mm / terminal]:	6 mm
Connection cold / hot water:	Rp 1 1/4"
Connection heat generator [thread]:	Rp 1 1/2"
Connection heat exchanger [thread]:	Rp 1"
Connection heating element [thread]:	Rp 1 1/2"
Max. immersion depth of screw-in heater [mm]:	1100