



Fresh-water storage tank for highest demands on drinking water hygiene and energy efficiency.

The structure of the storage tank is fundamentally different from usual large-volume domestic hot-water tanks. A built-in corrugated stainless steel pipe separates the drinking water from the heating water, while serving as a powerful heat exchanger at the same time. Thus, the advantages of a buffer tank are combined with those of a continuous flow water heater.

The heating water serves as actual heat storage while the drinking water flows through the corrugated stainless steel pipe only if required and, thus, a legionella-safe domestic water heating is ensured. You do not need a protection programme against legionella in the controller. At all times, the consumer is provided with hygienically clean, fresh water at the desired temperature.

## Data pursuant to EU regulation 814/2013

Name of supplier's trade marks:	OEG GmbH
Model identification of the supplier:	516008235 - Fresh-water storage tank 1,000 litres
Heat retaining losses in watts:	55
Storage tank volume in litres:	996

## General

OEG Nr.:	516008235
Rated volume according to EN 12897:	1000
Colour:	silver
Insulation according to DIN 4102-1 Fire Protection Class B2:	removable segment insulation
Weight [kg]:	265
Total height including insulation [mm]:	2350
Diameter without insulation [mm]:	790
Diameter with insulation [mm]:	1015
Tilt height [mm]:	2280

## Energy

Heat retaining loss according to EN 12897 [W]:	55
Heat losses in stand-by mode according to DIN 12897 [kW/h / 24 h]:	1,320
Output capacity (45°C) [l]:	571
Performance indicator NL following DIN 4708:	6,40

## Tank

Real volume according to EN 12897 [l]:	996
p <sub>max</sub> Tank [bar]:	3
t <sub>max</sub> Tank [°C]:	95
t <sub>min</sub> Tank [°C]:	20

## DHW heat exchanger

DHW heat exchanger area [m²]:	8
DHW heat exchanger volume [l]:	34
p <sub>max</sub> DHW heat exchanger [bar]:	6
t <sub>max</sub> DHW heat exchanger [°C]:	95

## Connections

Connection layout:	90°
Connection sensor [Ø mm / terminal]:	6 mm
Connection cold / hot water:	Rp 1 1/4"
Connection heat generator [thread]:	Rp 1 1/2"
Connection heating element [thread]:	Rp 1 1/2"
Max. immersion depth of screw-in heater [mm]:	800