

Pure+ Built-under fresh-water storage tank 80 litres vertical with upward connections



Fulfill your customers' highest demands when it comes down to drinking water hygiene and efficiency - with the vertical OEG built-under fresh-water storage tanks!

The structure of OEG fresh-water storage tanks is fundamentally different from usual large-volume domestic hot-water tanks. A built-in corrugated stainless steel pipe separates the drinking water from the heating water, while serving as a powerful heat exchanger at the same time. Thus, the advantages of a buffer tank are combined with those of a continuous flow water heater.

The drinking water flows through the corrugated stainless steel pipe in the water of the heated tank only if required. This leads to a very low energy consumption, and you can guarantee your customers legionella-free drinking water. You do not need a protection programme against legionella in the control unit. At all times, the consumer is provided with hygienically clean, fresh water in the desired temperature.

The storage tank has been designed with upward connections, and due to its compact design, it is particularly suitable for the heating of domestic water as built-under fresh-water storage tank with wall-hung boilers. Dimensions have been chosen such that it can be installed as a replacement for the built-under tanks of other well-known manufacturers. Also as a new installation in conjunction with wall-hung boilers, this storage tank can show its advantages.

The vertical (standing), compact design allows for the use in places that must be ruled out for other storage tanks (e.g. below inclined walls and stairs). Thus, your customers can benefit from the advantages of a fresh-water storage tank even if space is limited.

The generously dimensioned heat exchanger surfaces provide a huge energetic advantage compared to other products available on the market.

Data pursuant to EU regulation 812/2013

Name of supplier's trade marks:	OEG GmbH
Model identification of the supplier:	516005740 - Built-under fresh-water storage tank 80 litres vertical with upward connections
Heat retaining losses in watts:	23
Storage tank volume in litres:	80

General

OEG Nr.:	516005740
Rated volume according to EN 12897:	80
Colour:	white
Insulation according to DIN 4102-1 Fire Protection Class B2:	solid foamed insulation
Weight [kg]:	35
Total height including insulation [mm]:	620
Diameter with insulation [mm]:	610
Tilt height [mm]:	850

Pure+ Built-under fresh-water storage tank 80 litres vertical with upward connections



Energy

Heat retaining loss according to EN 12897 [W]:	23
Heat losses in stand-by mode according to DIN 12897 [kW/h / 24 h]:	0,552
Output capacity (45°C) [l]:	50
Performance indicator NL following DIN 4708:	0,60

Tank

Real volume according to EN 12897 [l]:	80
p _{max} Tank [bar]:	3
t _{max} Tank [°C]:	95
t _{min} Tank [°C]:	20

DHW heat exchanger

DHW heat exchanger area [m²]:	1,40
DHW heat exchanger volume [l]:	6
p _{max} DHW heat exchanger [bar]:	6
t _{max} DHW heat exchanger [°C]:	95

Connections

Connection layout:	connections at the top
Connection sensor [Ø mm / terminal]:	6 mm
Connection cold / hot water:	Rp 1 1/4"
Connection heat generator [thread]:	R 1"