

OEG Gerätebau GmbH

Industriestrasse 1-5, 49536 Lienen, Germany
Tel: +49 5483 727-0 Fax: +49 5483 727-500
eMail: verkauf@oeg.de



Die Ölversorgung mit
OEG Gerätebau GmbH
Der sicherste Weg zwischen
Tank und Brenner

Sales-office:

Winkelriedstr. 13a, 76185 Karlsruhe
Tel: +49 721 9613225 Fax: +49 721 9613226
eMail: karlsruhe@oeg.de

technical - data sheet

Order no.

120516060

Designation:

SMG 1606, OEG motor pump group

Description:

For light or heavy heating oil

Viscosity: max 80mm²/s

Temperature: up to 180° C

Pressure variation in operation and
on restart: max 5% of set pressure

Max pressure in feed line: 4 bar

Internal gear pump, with built-in pressure
regulating valve, return to tank feature,
self-priming, with shaft-seal

Three-phase current-foot and flange motor

Rotation direction:

(looking on the shaft end):

DC = right, clock wise

IC = left, anti clock wise

On standard at the motor-pump-groups

is a DC pump mounted

Pressure regulating valve:

Pressure range: with spez. spring 2: 2 to 9 bar

TÜV-checked at DIN 4736

Pressure max. 9 bar

Max. under pressure in suction line: -0,6 bar,

risk of air/gas separation below -0,4 bar

Pump-type: VBGRM, (KSVB450R, 070H1070)

Swept volume: 450 l/h at 6 bar

Connection: G: 1/2"

Power rating: 0,25 kW

Operating voltage: 240/400 V, 50 Hz

Speed: 1400 min⁻¹, System of protection: IP 54

Manufacture: OEG Gerätebau GmbH

Fon: +49 5483/727-0 or +49 721/9613225

Fax: +49 5483/727-500 or +49 721/9613226



Notes:

28.11.2001