## SilentMaster 110-8-6 WOF A311001

Product specification sheet





| Technical Data         | A311001                 |
|------------------------|-------------------------|
| Air displacement       | 105 l/min               |
| Max. free air delivery | 68 l/min                |
| Max. pressure          | 8 bar                   |
| Cylinder/Stage         | 1/1                     |
| Tank capacity          | 6 I                     |
| Voltage                | 230 V/50 Hz             |
| Motor output           | 0,75 kW                 |
| Drive                  | 1.450 min <sup>-1</sup> |
| Noise level            | 85 db(A)                |
| Dimenions<br>(WxDxH)   | 430 x 210 x 430<br>mm   |
| Weight                 | 18 kg                   |

### Product description

Fact Sheet

- Soundproof, portable, direct driven and oil free piston compressor
- For applications up to 8 bar
- This high quality performing air compressor for private and professional use
- Equipped with pressure reducer and gauges for measuring tank and outlet pressure
- With extra lifting handle on the tank
- Applications: Using smaller sized staple and nail guns, blow out guns, cartridge guns, grease and rivet guns

# SilentMaster 110-8-6 WOF A311001

Product specification sheet



Silent run and perfect cooling due to approved direct driven oil free aggregate and ideal cooling air flow

#### **Convenient transportation**

is provided by optimized center of gravity and carrying handle perfectly fitted

#### Precise working due

to filter pressure reducer for controlling the air pressure perfectly

#### Working

**comfortably** with perfect overview two pressure gauges for measuring tank and outlet pressure

#### Long service life

thanks to the 10 years anti-corrosion warranty on the compressed air tank

#### \_

Sturdy cover protects

aggregate from bumps

Robust

and knocks

Simple to handle easily accessible drain valve provides manual drainage of the condensate

Solid stand and comfort transportation due to large rubber feet

#### Further information

| Operates fully<br>automatically | On-off switch   |
|---------------------------------|---|
| Scope of delivery               | Instruction manual  |
| Warranty                        | 12 months for industrial use<br>24 months for private (non-commercial) use<br>36 months when registrated online |