

# OEG Buffer storage tank 2,600 l 1 smooth-pipe heat exchanger silver



This buffer storage tank fulfills the highest demands on heat storage, particularly where heat generators are used which achieve their optimal efficiency only under full load (e.g. many solid fuel boilers). During the operation of the heat generator, more heat is produced than the consumers can take. The excess heat heats the water of the buffer tank and is therefore stored. During later stand-still periods this heat can be retrieved, as needed.

The buffer storage tank is suitable as a primary cylinder for solar systems, heat pumps, wood- or pellet boilers and can also be used in district heating systems. Due to the additional smooth-pipe exchanger, another heat generator can be integrated, and its energy can be fed into the buffer tank additionally.

## General

|  |  |
|--|--|
| OEG Nr.:   | 516005402                                    |
| Rated volume according to EN 12897:                          | 2600   |
| Colour:  | silver                                       |
| Insulation according to DIN 4102-1 Fire Protection Class B2: | removable PES fleece insulation 0.036 W/(mK) |
| Weight [kg]:   | 400  |
| Total height including insulation [mm]:                      | 2490   |
| Diameter without insulation [mm]:                            | 1250   |
| Diameter with insulation [mm]:                               | 1450   |
| Tilt height [mm]:  | 2530   |

## Tank

|                        |    |
|------------------------|----|
| $p_{\max}$ Tank [bar]: | 3  |
| $t_{\max}$ Tank [°C]:  | 95 |
| $t_{\min}$ Tank [°C]:  | 20 |

## Smooth-pipe heat exchanger

|  |      |
|--|------|
| Smooth-pipe heat exchanger [number]:         | 1    |
| Smooth-pipe heat exchanger area bottom [m²]: | 5,90 |
| Smooth-pipe heat exchanger volume bottom:    | 39   |
| $p_{\max}$ Smooth-pipe heat exchanger [bar]: | 10   |
| $t_{\max}$ Smooth-pipe heat exchanger [°C]:  | 130  |

OEG Buffer storage tank 2,600 l 1 smooth-pipe  
heat exchanger silver



Connections

|   |           |
|---|-----------|
| Connection layout:                            | 90°       |
| Connection sensor [Ø mm / terminal]:          | 6 mm      |
| Connection heat generator [thread]:           | Rp 1 1/2" |
| Connection heat exchanger [thread]:           | Rp 1"     |
| Max. immersion depth of screw-in heater [mm]: | 1300      |