Commercial Product Name: PUP B1 750 Premium B1 Gun Foam

Revision Date: 15.09.2016 Replaces version from: 15.09.2016

Version: 4.1 /en Print date: 15.09.2016

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

#### 1.1 Product identifier

**Commercial Product Name** PUP B1 750 Premium B1 Gun Foam

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Foaming at constructional elements requiring advanced fire security

> standards, foaming in thermal insulation composite systems between EPS heat insulation panels, gaps of maximum 70 x 20 mm (depth x width), covered with mineral plaster, ideal construction and insulation foam for filling and sealing of cavities between brick work and window frames, window sills, roller blinds chassis etc., insulating of

pipeline mountings.

Recommended restrictions None under normal processing. Observe technical data sheet.

# 1.3 Details of the supplier of the safety data sheet

Company designation fischerwerke GmbH & Co. KG

> Klaus-Fischer-Straße 1 D-72178 Waldachtal

Telephone: +49(0)7443 12-0 FAX: +49(0)7443 12-4222 Email: info-sdb@fischer.de Internet: www.fischer.de

Marketer Great Britain: Mrs Mirka Valovicova, fischer Fixing (UK) Ltd, Hithercroft

Road, Wallingford, Oxfordshire, OX10 9AT, Tel. 01491 827 920, Fax

01491 827 950

#### 1.4 Emergency telephone number

Emergency telephone number +49(0)6132-84463 (24h)

#### **SECTION 2: Hazards identification**

# 2.1 Classification of the substance or mixture

Classification according to Reg-Flam. Aerosol 1; H222 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. ulation (EC) No. 1272/2008 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT

SE 3; H335 STOT RE 2; H373

#### 2.2 Label elements

Hazard pictogram







Commercial Product Name: PUP B1 750 Premium B1 Gun Foam

Revision Date: 15.09.2016 Replaces version from: 15.09.2016 Print date: 15.09.2016 Version: 4.1 /en

Signal word Danger

Hazardous component(s) to be

indicated on label

4, 4'-methylenediphenyl diisocyanate, isomers and homologues

H-statement(s) H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eve irritation.

H332: Harmful if inhaled.

H334: May cause allergy or asthma symptoms or breathing difficulties

if inhaled.

H335: May cause respiratory irritation. H351: Suspected of causing cancer.

H373: May cause damage to organs through prolonged or repeated

exposure.

P101: If medical advice is needed, have product container or label at P-statement(s)

P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face

protection.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

P405: Store locked up.

P410+P412: Protect from sunlight. Do no expose to temperatures ex-

ceeding 50 °C/122 °F.

P501: Dispose of contents/container to special waste treatment

Further information EUH204: Contains isocyanates. May produce an allergic reaction.

> Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children. Buildup of explosive mixtures possible without sufficient

ventilation.

Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma,

Commercial Product Name: PUP B1 750 Premium B1 Gun Foam

Revision Date: 15.09.2016

Replaces version from: 15.09.2016

Version : 4.1 /en Print date : 15.09.2016

eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

2.3 Other hazards

Health hazard None known.

Particular information pertaining specific risk for human / enNone known.

vironment

Indication of danger None known.

Hazard precautions None known.

# **SECTION 3: Composition/information on ingredients**

#### Hazardous ingredients

Ingredient		Classification (EC) 1272/2008	Concentration
4,4'-methylenediphenyl di- isocyanate, isomers and homologues	CAS No.: 9016-87-9 REACH No.: The sub- stance does not require registration according to Regulation (EC) No 1207/2006 [REACH].	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 STOT RE 2; H373	25.0 – 50.0 %
tris(2-chloro-1- methylethyl) phosphate	CAS No.: 13674-84-5 EC-No.: 237-158-7 REACH No.: 01-2119486772-26, 01-2119447716-31	Acute Tox. 4; H302	10.0 – 25.0 %
isobutane	CAS No.: 75-28-5 EC-No.: 200-857-2 Index-No.: 601-004-00-0 REACH No.: 01-2119485395-27	Flam. Gas 1; H220 Press. Gas; H280	2.5 – 10.0 %
dimethyl ether	CAS No.: 115-10-6 EC-No.: 204-065-8 Index-No.: 603-019-00-8 REACH No.: 01-2119472128-37, 01-2119519269-33	Flam. Gas 1; H220 Press. Gas; H280	2.5 – 10.0 %
propane	CAS No.: 74-98-6 EC-No.: 200-827-9 Index-No.: 601-003-00-5 REACH No.: 01-2119486944-21	Flam. Gas 1; H220 Press. Gas; H280	< 2.5 %
2,2-dimethylpropan-1-ol, tribromo derivative	CAS No. : 36483–57–5 EC–No. : 253–057–0	Eye Irrit. 2; H319	< 2.5 %

## **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General advice If symptoms persist, call a physician.

Take off all contaminated clothing immediately.

Remove/Take off immediately all contaminated clothing.

Commercial Product Name: PUP B1 750 Premium B1 Gun Foam

Revision Date: 15.09.2016 Replaces version from: 15.09.2016
Version: 4.1 /en Print date: 15.09.2016

If inhaled IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

If unconscious place in recovery position and seek medical advice.

In case of skin contact

Use mechanical handling equipment.

IF ON SKIN: Gently wash with plenty of soap and water.

In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

If swallowed, seek medical advice immediately and show this contain-

er or label.

Clean mouth with water and drink afterwards plenty of water. Drink 1

or 2 glasses of water. Do NOT induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms No data available

## 4.3 Indication of any immediate medical attention and special treatment needed

Immediate medical attention No data available
Special medical treatment No data available

## **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media Carbon dioxide (CO2)

Dry powder

Foam

Water spray jet

Extinguishing media which must

not be used for safety reasons

High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

Special exposure hazards arising from the substance or preparation itself, its combustion prod-

Container may rupture on heating. Heating or fire can release toxic gas. May form explosive mixtures in air.

ucts, or released gases

## 5.3 Advice for firefighters

Special protective equipment for

firefighting

In the event of fire, wear self-contained breathing apparatus. In the event of fire and/or explosion do not breathe fumes.

Additional information on fire-

fighting

Fire residues and contaminated fire extinguishing water must be dis-

posed of in accordance with local regulations.

Commercial Product Name: PUP B1 750 Premium B1 Gun Foam

Revision Date: 15.09.2016 Replaces version from: 15.09.2016 Version: 4.1 /en

Print date: 15.09.2016

Keep containers and surroundings cool with water spray. Container

may rupture on heating.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas.

> Keep away from sources of ignition - No smoking. Keep people away from and upwind of spill/leak.

#### 6.2 Environmental precautions

**Environmental precautions** The product should not be allowed to enter drains, water courses or

Prevent spreading over a wide area (e.g. by containment or oil barri-

ers).

# 6.3 Methods and material for containment and cleaning up

Methods for cleaning up Soak up with inert absorbent material (e.g. sand, silica gel, acid

binder, universal binder, sawdust).

Allow to solidify, use mechanical handling equipment.

Ensure adequate ventilation. Do not flush with water.

#### 6.4 Reference to other sections

Reference to other sections See chapter 8/13

#### 6.5 Additional information

Other information Treat recovered material as described in the section "Disposal consid-

erations".

Dispose of in accordance with local regulations.

#### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Advice on safe handling Handle and open container with care.

Provide sufficient air exchange and/or exhaust in work rooms.

Vapours are heavier than air and may spread along floors.

BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50°C. Do not open by force or throw into fire

even after use. Do not spray on flames or red-hot objects.

Advice on protection against fire

and explosion

Pressurized container: Protect from sunlight and do not expose to

temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any other incandescent material.

Keep away from sources of ignition - No smoking.

In use, may form flammable/explosive vapour-air mixture. Take measures to prevent the build up of electrostatic charge.

Commercial Product Name: PUP B1 750 Premium B1 Gun Foam

Revision Date: 15.09.2016 Replaces version from: 15.09.2016 Version: 4.1 /en

Print date: 15.09.2016

# 7.2 Conditions for safe storage, including any incompatibilities

Storage space and container re-

Keep containers tightly closed in a cool, well-ventilated place.

quirements

Container may rupture on heating.

Store in accordance with local regulations.

German storage class LGK 2B (TRGS 510)

7.3 Specific end use(s)

installation foam . Further information: see technical data sheet. Specific use(s)

## SECTION 8: Exposure controls/personal protection

## 8.1 Control parameters

#### dimethyl ether

#### Great Britain

Long-term exposure	Long-term exposure	Short-term exposure	Short-term exposure	Source
value/ ppm	value/ mg/m3	value / ppm	value / mg/m3	
400	766	500	958	19

Source: 19 - EH40/2005 Workplace exposure limits (2011)

#### Europe

	Long-term exposure value/	Issuing date	Source
mg/m3	ppm		
1 920	1 000	2000/39	24

Source: 24 - DIRECTIVE 2009/161/EU

#### 8.2 Exposure controls

Respiratory protection In case of inadequate ventilation wear respiratory protection.

professional users (long contact): Wear protective gloves. Hand protection

Suitable material: butyl-rubber, Chloroprene, Nitrile rubber

PVC disposable gloves Unsuitable material:

Material thickness: >= 0.5 mmBreak through time: >120 min

Remarks: Replace when worn.

Reference substance: Request information on glove permeation properties from the glove

> supplier.. Be aware that in daily use the durability of a chemical resistant protective glove can be notably shorter than the break through time measured according to EN 374, due to the numerous outside in-

fluences (e.g. temperature).

private users (short contact):

Commercial Product Name: PUP B1 750 Premium B1 Gun Foam

Revision Date: 15.09.2016 Replaces version from: 15.09.2016
Version: 4.1 /en Print date: 15.09.2016

Suitable material: attached disposable gloves

Remarks: Use gloves once only.

Eye protection Tightly fitting safety goggles

Skin and body protection Wear suitable protective equipment.

Note: Choose body protection according to the amount and concentration

of the dangerous substance at the work place.

General protective and hygiene

measures

Smoking, eating and drinking should be prohibited in the application

area.

Avoid contact with skin, eyes and clothing. Take off all contaminated clothing immediately.

Do not breathe vapors, mist or gas.

Wash hands before breaks and at the end of workday. Keep away from food, drink and animal feedingstuffs. Use protective skin cream before handling the product.

Information on environmental

protection regulations

No special environmental precautions required.

## **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state Aerosol
Colour vellow

Odour characteristic

Odour threshold not determined

pH not applicable

Boiling point [°C] not applicable (aerosol)

Flash point [°C] < 100

Reference substance : Aerosol

Evaporation rate [kg/(s\*m²)] No data available

Explosion limits [Vol-%]

Lower limit: 1,7
Upper limit: 18,6

Vapour pressure [kPa] 6

Vapour density not determined

Density [g/cm<sup>3</sup>] 1,06

Relative density not determined

Water solubility [g/l] immiscible

Commercial Product Name: PUP B1 750 Premium B1 Gun Foam

Revision Date: 15.09.2016 Replaces version from: 15.09.2016
Version: 4.1 /en Print date: 15.09.2016

Solubility [g/l] No data available

Partition coefficient n-octanol /

not determined

water (log P O/W)

Autoinflammability not auto-flammable

Decomposition temperature [°C] not determined Viscosity, dynamic [kg/(m\*s)] not determined

Risk of explosion. In use, may form flammable/explosive vapour-air mixture.

Oxidising properties No data available

9.2 Other information

Ignition temperature [°C] 235

Relative vapour density (air=1) not determined

Solvent content [%] 0,6

Measuring method: organic solvent

## **SECTION 10: Stability and reactivity**

10.1 Reactivity

Thermal decomposition No decomposition if stored and applied as directed.

10.2 Chemical stability

Chemical stability Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid Container may rupture on heating.

No decomposition if used as directed.

10.5 Incompatible materials

Materials to avoid No dangerous reaction known under conditions of normal use.

10.6 Hazardous decomposition products

Hazardous decomposition prod- Carbon oxides

ucts nitrogen oxides (NOx)

Commercial Product Name: PUP B1 750 Premium B1 Gun Foam

Revision Date: 15.09.2016 Replaces version from: 15.09.2016 Version: 4.1 /en

Print date: 15.09.2016

# **SECTION 11: Toxicological information**

## 11.1 Information on toxicological effects

# **Hazardous ingredients**

## 4,4'-methylenediphenyl diisocyanate, isomers and homologues

Oral toxicity [mg/kg]	Test criterion	Test species	Remarks	Source
> 5000	LD50	rat	OECD 423	100

Source : 100 - 100

Dermal toxicity [mg/kg]	Test criterion	Test species	Source
> 5000	LD50	rabbit	100

Source: 100 - 100

Inhalative toxicity [mg/l]	Test criterion	Exposure duration	Source
1,5	LC50	4 h	100

Source : 100 - 100

Irritant effect on the respi- Irritant ratory tract

#### tris(2-chloro-1-methylethyl) phosphate

Oral toxicity [mg/kg]	Test criterion	Test species	Source
2800	LD50	rat	100

Source: 100 - 100

Dermal toxicity	Test criterion	Test species	Duration	Remarks	Source
[mg/kg]					
> 2000	LD50	rabbit	24 h	OECD 402	100

Source: 100 - 100

Inhalative toxicity [mg/l]	Test criterion	Test species	Exposure dura- tion	Note	Source
> 5	LC50	rat		OECD 403	100

Source: 100 - 100

#### **ISOBUTANE**

Oral toxicity [mg/kg]	Source
No data available	100

Source : 100 - 100

Dermal toxicity [mg/kg]	Source
No data available	100

Source: 100 - 100

Inhalative toxicity	Test criterion	Test species	Exposure duration	Source
[mg/l]				
> 50	LC50	rat	4 h	100

Commercial Product Name: PUP B1 750 Premium B1 Gun Foam

Revision Date: 15.09.2016 Replaces version from: 15.09.2016 Version: 4.1 /en

Print date: 15.09.2016

Source: 100 - 100

#### dimethyl ether

Inhalative toxicity [mg/l]	Test criterion	Test species	Exposure duration	Source
308	LC50	rat	4 h	100

Source: 100 - 100

#### propane

Oral toxicity [mg/kg]	Source
No data available	100

Source : 100 - 100

Dermal toxicity [mg/kg]	Source	
No data available	100	

Source : 100 - 100

Inhalative toxicity [mg/l]	Test criterion	Test species	Exposure duration	Source
20	LC50	rat	4 h	100

Source: 100 - 100

Irritant effect on skin Irritating to skin and mucous membranes

Irritant effect on eyes Irritating to eyes.

Sensitization May cause sensitization by inhalation and skin contact.

#### 11.2 Additional information

Other information (chapter 11.) The product itself has not been tested.

# **SECTION 12: Ecological information**

## 12.1 Toxicity

## Hazardous ingredients

#### 4,4'-methylenediphenyl diisocyanate, isomers and homologues

Toxicity to fish	Test criterion	Test species	Measuring	Exposure dura-	Source
[mg/l]			method	tion	
> 100	LC50	Brachydanio rerio	OECD Test Guide-	96 h	100
		(zebra fish)	line 203		

Source: 100 - 100

Toxicity to daph- nia [mg/l]	Test criterion	Test species	· •	Measuring method	Source
> 1000	EC50	Daphnia magna (Water flea)	24 h	OECD Test Guide- line 202	100

Commercial Product Name: PUP B1 750 Premium B1 Gun Foam

Revision Date: 15.09.2016 Replaces version from: 15.09.2016 Version: 4.1 /en

Print date: 15.09.2016

Source : 100 - 100

Toxicity to algae [mg/	Test criterion	Test species	Exposure duration	Source
[1]				
> 1640	ErC50:	Scenedesmus subspica-	72 h	100
		tus		

Source : 100 - 100

NOEC (daphnia) [mg/l]	Test species	Measuring method	Exposure duration	Source
> 10	Daphnia magna (Big	OECD 202	21 d	100
	water flea).			

Source : 100 - 100

## Ready degradability

## tris(2-chloro-1-methylethyl) phosphate

Toxicity to fish [mg/l]	Test criterion	Test species	Exposure duration	Source
98	LC50	Pimephales promelas	96 h	100
		(Pimephales promelas		
		(fathead minnow))		

Source : 100 - 100

Toxicity to daph- nia [mg/l]	Test criterion	Test species	Exposure dura- tion	Measuring method	Source
131	EC50	Daphnia magna (Water flea)	48 h	OECD Test Guide- line 202	100

Source: 100 - 100

Toxicity to algae [mg/l]	Test criterion	Test species	Exposure dura- tion	Measuring method	Source
82	EC50	Selenastrum capri-	72 h	OECD Test Guide-	100
		cornutum		line 201	

Source : 100 - 100

#### Ready degradability

#### **ISOBUTANE**

Toxicity to fish [mg/l]	Test criterion	Exposure duration	Source
27,98	LC50	96 h	100

Source : 100 - 100

Toxicity to daphnia	Test criterion	Test species	Exposure duration	Source
[mg/l]				
14,22		Daphnia magna (Big water flea).	48 h	100

Source : 100 - 100

Toxicity to algae [mg/	Test criterion	Test species	Exposure duration	Source
7,71		Scenedesmus quadri- cauda (Green algae)	96 h	100

Commercial Product Name: PUP B1 750 Premium B1 Gun Foam

Revision Date: 15.09.2016 Replaces version from: 15.09.2016 Version: 4.1 /en Print date: 15.09.2016

Source : 100 - 100

## Ready degradability

## dimethyl ether

Toxicity to fish [mg/l]	Test criterion	Exposure duration	Source
> 1000	LC50	96 h	100

Source : 100 - 100

Toxicity to daphnia [mg/l]	Test criterion	Test species	Exposure duration	Source
> 4400	LC50	Daphnia magna (Water flea)	48 h	100

Source : 100 - 100

Toxicity to algae [mg/	Test criterion	Test species	Exposure duration	Source
154,917		Scenedesmus quadri- cauda (Green algae)	96 h	100

Source : 100 - 100

#### Ready degradability

#### propane

Toxicity to fish [mg/l]	Test criterion	Exposure duration	Source
> 1000	LC50	96 h	100

Source : 100 - 100

Toxicity to daphnia [mg/l]	Test criterion	Test species	Exposure duration	Source
14,22		Daphnia magna (Big water flea).	48 h	100

Source : 100 - 100

Toxicity to algae [mg/	Test criterion	Test species	Exposure duration	Source
<b>I</b> ]				
7,71	EC50	Scenedesmus quadri-	96 h	100
		cauda (Green algae)		

Source : 100 - 100

#### Ready degradability

## 2,2-dimethylpropan-1-ol, tribromo derivative

Ready degradability

## 12.2 Persistence and degradability

Elimination and distribution

No information available.

mechanisms

Commercial Product Name: PUP B1 750 Premium B1 Gun Foam

Revision Date: 15.09.2016 Replaces version from: 15.09.2016
Version: 4.1 /en Print date: 15.09.2016

Elimination in purification plant No data available Biodegradability No data available

#### 12.3 Bioaccumulative potential

Bioaccumulation no data available
Bioconcentration factor (BCF) No data available

## 12.4 Mobility in soil

Distribution in the environment No data available

Mobility

Mobility: No data available

#### 12.5 Results of PBT and vPvB assessment

Results of PBT characteristics

determination

This preparation contains no substance considered to be persistent,

bioaccumulating nor toxic (PBT).

This preparation contains no substance considered to be very persis-

tent nor very bioaccumulating (vPvB).

#### 12.6 Other adverse effects

Further information on ecology 
The product itself has not been tested.

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Disposal considerations Disposal together with normal waste is not allowed. Special disposal

required according to local regulations.

The product should not be allowed to enter drains, water courses or

the soil.

Empty remaining contents.

Waste Code 080501 – waste isocyanates

160504 - gases in pressure containers (including halons) containing

dangerous substances

cured material: 200000 - MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS

Uncleaned empty packaging Dispose of as unused product.

# **SECTION 14: Transport information**

	Land transport ADR/RID	Marine transport IMDG	Air transport ICAO/IATA
14.1 UN-No	1950	1950	1950
14.2 Description of the goods	AEROSOLS	AEROSOLS	
14.2 UN proper shipping		AEROSOLS	Aerosols, flammable
name			

Commercial Product Name: PUP B1 750 Premium B1 Gun Foam

Revision Date: 15.09.2016

Version: 4.1 /en

Replaces version from: 15.09.2016

Print date: 15.09.2016

Land transport ADR/RID Marine transport IMDG Air transport ICAO/IATA 14.3 Transport hazard class(es) inflammable Remarks (maximum 1 L) flammable 2.1 Labels 2.1 2.1 Category Classification Code 5F Tunnel restriction code D 14.5 Environmental haz-0: Non-marine pollutant ards EmS F-D;S-U

## 14.6 Special precautions for user

Precautions not required under normal use

#### 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to not applicable

Annex II of MARPOL73/78 and

Stowage category

the IBC Code

# **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Additional regulations Persons already sensitised to diisocyanates may develop allergic re-

actions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

Water hazard class (self-classifi- 1

cation)

#### 15.2 Chemical safety assessment

Safety assessment Not relevant. Chemical safety assessments for substances in this mix-

ture were not carried out.

# **SECTION 16: Other information**

Relevant H-phrases H220: Extremely flammable gas.

H222: Extremely flammable aerosol.

H280: Contains gas under pressure; may explode if heated.

H302: Harmful if swallowed. H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

Commercial Product Name: PUP B1 750 Premium B1 Gun Foam

Revision Date: 15.09.2016 Replaces version from: 15.09.2016 Version: 4.1 /en

Print date: 15.09.2016

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H334: May cause allergy or asthma symptoms or breathing difficulties

if inhaled.

H335: May cause respiratory irritation. H351: Suspected of causing cancer.

H373: May cause damage to organs through prolonged or repeated

EUH204: Contains isocyanates. May produce an allergic reaction.

Wording of the hazard classes

Flam. Aerosol: Flammable aerosol

Acute Tox.: Acute toxicity Skin Irrit.: Skin irritation

Eye Irrit.: Serious eye irritation

Resp. Sens.: Respiratory sensitization

Skin Sens.: Skin sensitization

Carc.: Carcinogenicity

STOT SE: Specific target organ toxicity - single exposure STOT RE: Specific target organ toxicity - repeated exposure

Flam. Gas: Flammable gas

Press. Gas: Gases under pressure

Modifications since last version

Modifications of the previous version are denoted with an asterisk (\*).

Classification for mixtures and used evaluation method according to regulation (EC)

1272/2008 [CLP]

Classification	Evaluation	
Flam. Aerosol 1; H222	Experimental data	
Acute Tox. 4; H332	Calculated	
Skin Irrit. 2; H315	Calculated	
Eye Irrit. 2; H319	Calculated	
Resp. Sens. 1; H334	Calculated	
Skin Sens. 1; H317	Calculated	
Carc. 2; H351	Calculated	
STOT SE 3; H335	Calculated	
STOT RE 2; H373	Calculated	

Recommended restrictions

None under normal processing. Observe technical data sheet.

This information is provided in accordance with the current status of our knowledge and experience. The Safety Data Sheet describes products with a view to relevant safety requirements. This information does not constitute a warranty of properties, features or qualities.