

# Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 12

SDS No.: 357533

V001.0 Revision: 04.01.2019

printing date: 21.09.2020 Replaces version from: -

**LOCTITE 5776** 

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

LOCTITE 5776

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Anaerobic Adhesive

## 1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA

Henkelstr. 67

40589 Düsseldorf

Germany

Phone: +49 211 797 0 Fax-no.: +49 211 798 2009

ua-productsafety.de@henkel.com

## 1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

## **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

## Classification (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

#### 2.2. Label elements

## Label elements (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

**Supplemental information** EUH210 Safety data sheet available on request.

#### 2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

## **SECTION 3: Composition/information on ingredients**

## 3.2. Mixtures

## General chemical description:

Anaerobic adhesive

## Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Tributyl amine 102-82-9	203-058-7 01-2119474898-14	0,1-< 1 %	Acute Tox. 4; Oral H302
102-82-9	01-2119474696-14		Acute Tox. 2; Dermal
			H310
			Skin Irrit. 2
			H315
			Acute Tox. 1; Inhalation
			H330
Cumene hydroperoxide	201-254-7	0,1-< 1 %	Acute Tox. 4; Dermal
80-15-9	01-2119475796-19		H312
			STOT RE 2
			H373
			Acute Tox. 4; Oral
			H302
			Org. Perox. E
			H242
			Acute Tox. 3; Inhalation
			H331
			Aquatic Chronic 2
			H411
			Skin Corr. 1B
			H314
1,4-Naphthalenedione	204-977-6	0,0025-< 0,025 %	Acute Tox. 3; Oral
130-15-4		( 25 ppm- < 250 ppm)	H301
			Skin Irrit. 2; Dermal
			H315
			Skin Sens. 1; Dermal
			H317
			Eye Irrit. 2
			H319
			Acute Tox. 1; Inhalation
			H330
			STOT SE 3; Inhalation
			H335
			Aquatic Acute 1
			H400
			Aquatic Chronic 1 H410
			-
			M factor (Acute Aquat Tox): 10 M factor
			(Chron Aquat Tox): 10

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

## **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Seek medical advice.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion:

Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting.

Seek medical advice.

#### 4.2. Most important symptoms and effects, both acute and delayed

Prolonged or repeated contact may cause eye irritation.

Prolonged or repeated contact may cause skin irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

## **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### Suitable extinguishing media:

Carbon dioxide, foam, powder

#### Extinguishing media which must not be used for safety reasons:

None known

#### 5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.

#### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

#### **Additional information:**

In case of fire, keep containers cool with water spray.

#### **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

Avoid skin and eye contact.

Wear protective equipment.

Ensure adequate ventilation.

#### 6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

#### 6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Dispose of contaminated material as waste according to Section 13.

#### 6.4. Reference to other sections

See advice in section 8

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

Use only in well-ventilated areas.

Avoid skin and eye contact.

Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

See advice in section 8

#### Hygiene measures:

Good industrial hygiene practices should be observed.

Do not eat, drink or smoke while working.

Wash hands before work breaks and after finishing work.

#### 7.2. Conditions for safe storage, including any incompatibilities

Refer to Technical Data Sheet

# 7.3. Specific end use(s)

Anaerobic Adhesive

# **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

## **Occupational Exposure Limits**

Valid for

Germany

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Ethene, homopolymer 9002-88-4		1,25	Exposure limit(s):		TRGS 900
Ethene, homopolymer 9002-88-4			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Ethene, homopolymer 9002-88-4		10	Exposure limit(s):	2	TRGS 900
Silicon dioxide 112945-52-5		4	Exposure limit(s):	If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900

## **Predicted No-Effect Concentration (PNEC):**

Name on list	Environmental Compartment	Exposure period	Value	Value			Remarks
	•	•	mg/l	ppm	mg/kg	others	
Tributyl amine	aqua		0,0036	•			
102-82-9	(freshwater)		mg/l				
Tributyl amine	aqua (marine		0,00036				
102-82-9	water)		mg/l				
Tributyl amine	sediment				16,9 mg/kg		
102-82-9	(freshwater)						
Tributyl amine	sediment				1,69 mg/kg		
102-82-9	(marine water)						
Tributyl amine	aqua		0,036 mg/l				
102-82-9	(intermittent						
	releases)						
Tributyl amine 102-82-9	Soil				3,37 mg/kg		
Tributyl amine	sewage		100 mg/l				
102-82-9	treatment plant		100 mg/i				
102 02 9	(STP)						
.alpha.,.alphaDimethylbenzyl	aqua		0.0031				
hydroperoxide	(freshwater)		mg/l				
80-15-9	,						
.alpha.,.alphaDimethylbenzyl	aqua (marine		0,00031				
hydroperoxide	water)		mg/l				
80-15-9							
.alpha.,.alphaDimethylbenzyl	aqua		0,031 mg/l				
hydroperoxide	(intermittent						
80-15-9	releases)						
.alpha.,.alphaDimethylbenzyl	Sewage		0,35 mg/l				
hydroperoxide	treatment plant						
80-15-9					0.022		
.alpha.,.alphaDimethylbenzyl	sediment				0,023		
hydroperoxide 80-15-9	(freshwater)				mg/kg		
	sediment				0.0023		
.alpha.,.alphaDimethylbenzyl hydroperoxide	(marine water)				- ,		
80-15-9	(marme water)				mg/kg		
.alpha.,.alphaDimethylbenzyl	Soil				0,0029		
hydroperoxide	3011				mg/kg		
80-15-9					IIIg/ Kg		
00-13-7		1	l	l		1	

#### **Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
		1		Time		
Tributyl amine	Workers	inhalation	Long term		15,2 mg/m3	
102-82-9			exposure -			
			systemic effects			
Tributyl amine	Workers	inhalation	Long term		15,2 mg/m3	
102-82-9			exposure - local			
			effects			
.alpha.,.alphaDimethylbenzyl	Workers	inhalation	Long term		6 mg/m3	
hydroperoxide			exposure -			
80-15-9			systemic effects			

## **Biological Exposure Indices:**

None

## 8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Wear protective glasses.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

## **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Appearance paste

liquid yellow

Odor characteristic

Odour threshold No data available / Not applicable

pΗ No data available / Not applicable No data available / Not applicable Melting point Solidification temperature No data available / Not applicable No data available / Not applicable Initial boiling point > 100 °C (> 212 °F) Flash point

Evaporation rate No data available / Not applicable Flammability No data available / Not applicable No data available / Not applicable Explosive limits Vapour pressure No data available / Not applicable Relative vapour density: No data available / Not applicable No data available / Not applicable Density Bulk density No data available / Not applicable Solubility No data available / Not applicable No data available / Not applicable Solubility (qualitative) Partition coefficient: n-octanol/water No data available / Not applicable Auto-ignition temperature No data available / Not applicable Decomposition temperature No data available / Not applicable No data available / Not applicable Viscosity Viscosity (kinematic) No data available / Not applicable No data available / Not applicable

#### 9.2. Other information

Explosive properties

Oxidising properties

No data available / Not applicable

## **SECTION 10: Stability and reactivity**

No data available / Not applicable

#### 10.1. Reactivity

Peroxides.

#### 10.2. Chemical stability

Stable under recommended storage conditions.

## 10.3. Possibility of hazardous reactions

See section reactivity

#### 10.4. Conditions to avoid

Stable under normal conditions of storage and use.

#### 10.5. Incompatible materials

See section reactivity.

## 10.6. Hazardous decomposition products

carbon oxides.

## **SECTION 11: Toxicological information**

## General toxicological information:

Prolonged or repeated contact may cause skin irritation.

Prolonged or repeated contact may cause eye irritation.

## 11.1. Information on toxicological effects

#### Acute oral toxicity:

May cause irritation to the digestive tract.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Tributyl amine 102-82-9	LD50	320 mg/kg	mouse	
Tributyl amine 102-82-9	LD50	420 mg/kg	rat	not specified
Cumene hydroperoxide 80-15-9	LD50	550 mg/kg	rat	not specified
1,4-Naphthalenedione 130-15-4	LD50	190 mg/kg	rat	not specified

## Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Species	Method
CAS-No.	type			
Tributyl amine 102-82-9	LD50	195 mg/kg	rabbit	not specified
Cumene hydroperoxide 80-15-9	LD50	1.200 - 1.520 mg/kg		not specified

### Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Tributyl amine 102-82-9	LC50	0,5 mg/l	vapour	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)

## Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Cumene hydroperoxide	corrosive		rabbit	Draize Test
80-15-9				

## Serious eye damage/irritation:

No data available.

## Respiratory or skin sensitization:

No data available.

## Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Cumene hydroperoxide 80-15-9	positive	bacterial reverse mutation assay (e.g Ames test)	without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)

## Carcinogenicity

No data available.

## Reproductive toxicity:

No data available.

## STOT-single exposure:

No data available.

## STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Cumene hydroperoxide 80-15-9		inhalation: aerosol	6 h/d 5 d/w	rat	not specified

## Aspiration hazard:

No data available.

# **SECTION 12: Ecological information**

#### **General ecological information:**

Do not empty into drains / surface water / ground water.

## 12.1. Toxicity

## **Toxicity (Fish):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Tributyl amine 102-82-9	LC50	60,2 mg/l	48 h	Leuciscus idus	DIN 38412-15
Cumene hydroperoxide 80-15-9	LC50	3,9 mg/l	96 h	, ,	OECD Guideline 203 (Fish, Acute Toxicity Test)

## Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Tributyl amine	EC50	8 mg/l	48 h	Daphnia magna	OECD Guideline 202
102-82-9					(Daphnia sp. Acute
					Immobilisation Test)
Cumene hydroperoxide	EC50	18 mg/l	48 h	Daphnia magna	OECD Guideline 202
80-15-9					(Daphnia sp. Acute
					Immobilisation Test)

## Chronic toxicity to aquatic invertebrates

No data available.

## Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Tributyl amine 102-82-9	EC10	1,378 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Tributyl amine 102-82-9	EC50	8,215 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Cumene hydroperoxide 80-15-9	ErC50	3,1 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
1,4-Naphthalenedione 130-15-4	EC50	0,011 mg/l	72 h	Dunaliella bioculata	OECD Guideline 201 (Alga, Growth Inhibition Test)

#### Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value	Value	Exposure time	Species	Method
	type				
Tributyl amine	EC0	> 800 mg/l	3 h		OECD Guideline 209
102-82-9					(Activated Sludge,
					Respiration Inhibition Test)
Cumene hydroperoxide	EC10	70 mg/l	30 min		not specified
80-15-9					•

## 12.2. Persistence and degradability

The product is not biodegradable.

Hazardous substances	Result	Test type	Degradability	Exposure	Method
CAS-No.				time	
Tributyl amine		aerobic	< 10 %	15 d	OECD Guideline 301 C (Ready
102-82-9					Biodegradability: Modified MITI
					Test (I))
Tributyl amine	inherently biodegradable	aerobic	94 %	15 d	OECD Guideline 302 B (Inherent
102-82-9					biodegradability: Zahn-
					Wellens/EMPA Test)
Tributyl amine	readily biodegradable	aerobic	80,3 %	29 d	OECD Guideline 301 B (Ready
102-82-9					Biodegradability: CO2 Evolution
					Test)
Cumene hydroperoxide		no data	0 %	28 d	OECD Guideline 301 B (Ready
80-15-9					Biodegradability: CO2 Evolution
					Test)
1,4-Naphthalenedione		no data	0 - 60 %		OECD 301 A - F
130-15-4					

## 12.3. Bioaccumulative potential

No data available.

Hazardous substances	Bioconcentratio	Exposure time	Temperature	Species	Method
CAS-No.	n factor (BCF)		_		
Cumene hydroperoxide	9,1			calculation	OECD Guideline 305
80-15-9					(Bioconcentration: Flow-through
					Fish Test)

## 12.4. Mobility in soil

Cured adhesives are immobile.

Hazardous substances	LogPow	Temperature	Method
CAS-No.			
Tributyl amine	3,338	25 °C	OECD Guideline 123 (Partition Coefficient (1-Octanol / Water), Slow-
102-82-9			Stirring Method)
Cumene hydroperoxide	2,16		not specified
80-15-9			
1,4-Naphthalenedione	1,71		not specified
130-15-4			

## 12.5. Results of PBT and vPvB assessment

Hazardous substances	PBT / vPvB
CAS-No.	
Tributyl amine	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
102-82-9	Bioaccumulative (vPvB) criteria.
Cumene hydroperoxide	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
80-15-9	Bioaccumulative (vPvB) criteria.
1,4-Naphthalenedione	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
130-15-4	Bioaccumulative (vPvB) criteria.

## 12.6. Other adverse effects

No data available.

# **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

Product disposal:

Dispose of in accordance with local and national regulations.

Contribution of this product to waste is very insignificant in comparison to article in which it is used

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

#### Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

## **SECTION 14: Transport information**

#### 14.1. UN number

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

## 14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

### 14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

#### 14.4. Packing group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

## 14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

#### 14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

## 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

## **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content (2010/75/EC)

< 3 %

## 15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

#### National regulations/information (Germany):

WGK: WGK = 2, significantly water endangering mixture. Classification according to

the mixture rules in German AwSV regulation annex 1, number 5.2 from 18.

April 2017.

10

Storage class according to TRGS 510:

## **SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

H242 Heating may cause a fire.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H310 Fatal in contact with skin.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

#### **Further information:**

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.