

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Version: 3.3, ID-No.: 2100-g-01_GB-GB

Revision date 01.08.2020

Page 1/8

SECTION 1: Identification of the substance/mixture and of the company TYFOCOR® GE 1.1. Product identifier: 1.2. Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses: Antifreeze and anti-corrosion fluid for thermotechnical systems 1.3. Details of the supplier of the safety data sheet TYFOROP Chemie GmbH, Ausschläger Billdeich 77, D-20539 Hamburg Company: **Telephone/Telefax:** Tel.: +49 (0)40 20 94 97 0, Fax: +49 (0)40 20 94 97 20 E-Mail: msds@tyfo.de (E-Mail adress of person responsible for SDS) 1.4. Emergency telephone number: Tel.: +49 (0)551-19240 GIZ-Nord Poison Center SECTION 2: Hazards identification 2.1. Classification of the substance or mixture Classification according to Regulation (EC) No. 1272/2008 [CLP] Acute Tox. 4, H302. STOT RE 2, H373. The full text of the abbreviations is listed in section 16. 2.2. Label elements Labelling according to Regulation (EC) No. 1272/2008 [CLP] Signal word Hazard pictograms Warning **Hazard Statements** H302 Harmful if swallowed H373 May cause damage to kidneys through prolonged or repeated exposure by swallowing **Precautionary Statements (Prevention)** P260 Do not breathe vapour/mist/aerosol P264 Wash skin with plenty of water and soap thoroughly after handling P270 Do not eat, drink or smoke when using this product **Precautionary Statements (Response)** P312 Call a POISON CENTER or doctor/physician if you feel unwell P301+P330 IF SWALLOWED: rinse mouth **Precautionary Statements (Disposal)** P501 Dispose of contents/container to hazardous or special waste collection point Hazard determinant component for labelling Ethane-1,2-diol / Ethylene glycol 2.3. Other hazards: None known. **SECTION 3: Composition/information on ingredients** 3.2. Mixtures Chemical nature: Ethane-1,2-diol (ethylene glycol). Inhibitors. Hazardous components Substance / REACH Content **CAS** number EC number **INDEX** number Classification acc. registration number CLP 603-027-00-1 >90 % 107-21-1 203-473-3 Acute Tox. 4, H302 Ethane-1.2-diol 01-2119456816-28 STOT RE 2, H373 The full text of the abbreviations is listed in section 16.

SECTION 4: First aid measures

4.1. Description of first aid mea	4.1. Description of first aid measures				
General advice:	In the case of an accident or if you feel unwell, seek medical advice im- mediately. If symptoms persist or in cases of doubt seek medical advice.				
Protection of first-aiders:	First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.				
If inhaled:	If inhaled, remove to fresh air. Get medical attention if symptoms occur.				
On skin contact:	Wash thoroughly with soap and water. Get medical attention if symp- toms occur.				
On contact with eyes:	On contact with eyes: Wash affected eyes for at least 15 minutes under running water with eye- lids held open. Get medical attention if irritation develops and persists.				
On ingestion:	On ingestion: Immediately rinse mouth thoroughly with water. Get medical attention DO NOT induce vomiting unless directed to do so by medical personnel. Administer 50 ml of pure ethanol in a drinkable concentration.				
	and effects, both acute and delayed toms and effects are described in sections 2 and/or 11. Further important not known.				
4.3. Indication of any immediat	e medical attention and special treatment needed				
Treatment:	Symptomatic treatment (decontamination, vital functions).				
SECTION 5: Firefighting measu	SECTION 5: Firefighting measures				
5.1. Extinguishing media					
Suitable extinguishing media: Unsuitable extinguishing media	Water spray. Alcohol-resistant foam. Dry powder. Carbon dioxide (CO ₂). a: None known.				
5.2. Special hazards arising fro	om the substance or mixture				
Specific hazards during firefighting:	Exposure to combustion products may be a hazard to health.				
Hazardous combustion produc	ts: Carbon oxides.				
5.3. Advice for fire-fighters					
Special protective equipment:	Special protective In the event of fire, wear self-contained breathing apparatus. Use per-				

equipment.	sonal protective equipment.
Specific extinguishing	Use extinguishing measures that are appropriate to local circumstances
methods:	and the surrounding environment. Use water spray to cool unopened con-
	tainers. Remove undamaged containers from fire area if it is safe to do so.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Use personal protective ec

Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.

6.2. Environmental precautions

Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up: Soak up with inert absorbent material. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.

Version: 3.3, ID-No.: 2100-g-01_GB-GB

SECTION 6: Accidental release measures - Continuation

Sections 13 and 15 provide information regarding certain local or national requirements.

6.4. Reference to other sections: See sections 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handli	ing
Technical measures:	See Engineering measures in section 8.
Local/total ventilation:	Use only with adequate ventilation.
Advice on safe handling:	Avoid inhalation of vapour or mist. Do not swallow. Avoid contact with eyes. Avoid repeated or prolonged contact with skin. Handle in accordance with good industrial hygiene and safety practice. Shut containers immediately after taking product because product takes up the humidity of air. Take care to prevent spills, waste and minimize release to the environment.
Advice on protection against fire and explosion:	Observe the general rules of industrial fire protection.
Hygiene measures:	When using do not eat, drink or smoke. Wash contaminated clothing be- fore re-use.
7.2. Conditions for safe storage	e, including any incompatibilities
Requirements for storage areas and containers:	Store containers tightly sealed in a cool, dry and well ventilated place. Store in accordance with the particular national regulations.
Advice on common storage:	Do not store with strong oxidizing agents. Keep away from food, beve- rages and animal feedstuffs.

7.3. Specific end uses

For the relevant identified uses listed in section 1 the advice mentioned in this section 7 is to be observed.

SECTION 8: Exposure control/personal protection

8.1. Control parameters

Components with occupational exposure limits Information on component Ethane-1,2-diol

Legal basis	Value type	Control parameters	Further information
2000/39/EC	TWA STEL	52 mg/m ³ , 20 ppm 104 mg/m ³ , 40 ppm	Identifies the possibility of significant uptake through the skin, indicative.
GB EH40	TWA (Vapour) TWA (Particles) STEL (Vapour)	52 mg/m³, 20 ppm 10 mg/m³ 104 mg/m³, 40 ppm	Can be absorbed through skin. The assigned sub- stances are those for which there are concerns that dermal absorption will lead to systemic toxicity.

DNEL values - information on component Ethane-1,2-diol

End use	Exposure routes	Potential health effects	Value
Workers	Inhalation	Long-term local effects	35 mg/m ³
Workers Consumers	Skin contact Inhalation	Long-term systemic effects Long-term local effects	106 mg/kg body weight/day 7 mg/m³
Consumers	Skin contact	Long-term systemic effects	53 mg/kg body weight/day

PNEC values - information on component Ethane-1,2-diol

Fresh water	Marine water	Water (intermit- tent release)	Fresh water sediment	Marine water sediment	Soil	Sewage treat- ment plant
10 mg/l	1 mg/l	10 mg/l	37 mg/kg	3.7 mg/kg	1.53 mg/kg	199.5 mg/l

Version: 3.3, ID-No.: 2100-g-01_GB-GB

SECTION 8: Exposure control/personal protection - Continuation

8.2. Exposure controls	
Engineering measures:	Ensure adequate ventilation, especially in confined areas. Minimize work- place exposure concentrations.
Personal protective equipment	
Eye protection:	Safety glasses with side-shields (frame goggles, e.g. EN 166).
Hand protection:	Chemical resistant protective gloves (EN 374). Material: butyl rubber. Protective index 6. Break through time: >480 minutes. Glove thickness: 0.6-0.8 mm. Remarks: Choose gloves to protect hands against chemi- cals depending on the concentration and quantity of the hazardous sub- stance and specific to place of work. For special applications, we re- commend clarifying the resistance to chemicals of the aforementioned protective gloves with the manufacturer. Wash hands before breaks and at the end of workday.
Skin and body protection:	Wash skin thoroughly after contact.
Respiratory protection:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Filter type: Organic vapour type (A).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

9.1. Information on basic physic	cal and chemical properties	
Appearance:	liquid.	
Colour:	green.	
Odour:	almost odourless.	
Odour threshold:	No data available.	
pH value (20 °C):	8.0 - 8.5.	(ASTM D 1287)
Solidification temperature:	<-18 °C.	(DIN ISO 3016)
Initial boiling point/boiling range:	>170 °C.	(ASTM D 1120)
Flash point:	>110 °C.	(DIN EN 22719, ISO 2719)
Evaporation rate:	No data available.	
Flammability (solid, gas):	not applicable.	
Upper explosion limit:	15.0 % vol.	(Inform. on Ethylene glycol)
Lower explosion limit:	3.2 % vol.	(Inform. on Ethylene glycol)
Vapour pressure (20 °C):	ca. 0.2 hPa.	(calculated)
Vapour density:	No data available.	
Density (20 °C):	ca. 1.10 - 1.13 g/cm³.	(DIN 51757)
Solubility:	Water solubility: soluble.	
Partition coefficient n-octanol/H ₂ O:	: log P _{ow} : -1.93.	(Inform. on Ethylene glycol)
Auto-ignition temperature:	No data available.	
Decomposition temperature:	No data available.	
Viscosity (kinematic, 20 °C):	24 - 28 mm²/s.	(DIN 51562)
Explosive properties:	not explosive.	
Oxidizing properties:	not oxidizing.	
9.2. Other Information		
Hygroscopy:	hygroscopic.	

SECTION 10: Stability and reactivity

10.1. Reactivity:	No hazardous reactions if stored and handled as prescribed/indicated. Corrosion to metals: No corrosive effect on metals.
10.2. Chemical stability:	The product is stable if stored and handled as prescribed/indicated.
10.3. Possibility of hazar- dous reactions:	No hazardous reactions if stored and handled as prescribed/indicated.
10.4. Conditions to avoid:	No conditions to avoid anticipated.
10.5. Incompatible materials:	Substances to avoid: strong oxidising agents.
10.6. Hazardous decom- position products:	No hazardous decomposition products if stored and handled as pres- cribed/indicated.

TYFOROP Safety Data Sheet Product: TYFOCOR[®] GE Version: 3.3, ID-No.: 2100-g-01_GB-GB

SECTION 11: Toxicological information

	11.1. Information on toxicological effects				
	Information on likely	Inhalation. Skin contact. Ingestion. Eye contact.			
	routes of exposure:				
1	Acute toxicity:	Harmful if swallowed. Information on the product: Acute oral toxicity: ATE: 52 method: calculation method.			
		Information on component Ethane-1,2-diol: Acute oral to 500 mg/kg, method: expert judgement. Remark: Based or ed classification in Reg. (EC) No. 1272/2008, Annex VI. lation toxicity: LC50 (Rat): >2.5 mg/l, exposure time: 4 ho ment: The substance has no acute inhalation toxicity. Ac toxicity LD50 (Mouse): >3500 mg/kg.	on harmonis- Acute inha- urs. Assess-		
I	Skin corrosion/ irritation:	Not classified based on available information. Information on component Ethane-1,2-diol: No skin irrita	ation (Rabbit).		
I	Serious eye damage/ eye irritation:	Not classified based on available information. Information on component Ethane-1,2-diol: No eye irrita	ition (Rabbit).		
I	Respiratory or skin sensitisation:	Skin sensitisation: Not classified based on available information. Res- biratory sensitisation: Not classified based on available information. nformation on component Ethane-1,2-diol: Skin contact: not sensiti- sing (Guinea pig, Maximisation Test (GPMT)).			
I	Germ cell mutagenicity:	Not classified based on available information. Information on component Ethane-1,2-diol: Genotoxicity mutagenic (Bacteria, AMES Test), method: OECD test gu			
	Carcinogenicity:	Not classified based on available information. Information on component Ethane-1,2-diol: not carcinog application route: ingestion, exposure time: 2 years.	genic (Mouse),		
I	Reproductive toxicity:	Not classified based on available information.			
	Specific target organ toxi- city (single exposure):	Not classified based on available information.			
	Specific target organ toxi- city (repeated exposure):	May cause damage to kidneys through prolonged or rep sure by swallowing. Information on component Ethane-1,2-diol: Target organ sessment: Shown to produce significant health effects in a centrations of >10-100 mg/kg body weight, exposure ro	n: Kidney. As- animals at con-		
I	Repeated dose toxicity:	Information on component Ethane-1,2-diol: NOAEL (Ra application route: ingestion, exposure time: 2 years. N 2200 - 4400 mg/kg, application route: skin contact, exp weeks, method: OECD test guideline 410.	OAEL (Dog):		
	Aspiration toxicity:	Not classified based on available information.			
	Other information:	Information on Ethane-1,2-diol: Experimental/calculated data thal dose: 1.2 - 1.5 g/kg body weight, oral, adults. The sympt nosis/findings mentioned may result with smaller doses.			
	Potential effects	Symptoms	Period of time		
	on central nervous system (CNS) and gastrointestinal tract	seizures, convulsions, coma, respiratory arrest, circula- tory collapse	30 min - 12 h		
	on cardiac and pulmonary function	Acceleration of pulse and breathing, increased blood pres- sure, possibly inflammatory mucosal changes, pulmonary edema, congestive heart failure	12 - 24 h		
	Renal impairment	Oliguria to anuria, degeneration of the kidney tissue with oxalate crystal deposits	24 - 72 h		
	CNS degeneration	Double-sided facial paralysis, pupillary inequality, blurred vision, dysphagia, hyperreflexia, incoordination, cerebral	6 - 14 d		

oedema, deposit of calcium oxalate in the brain

oduct: TYFOCOR® GE			Page 6/8		
ECTION 12: Ecologica	al inform	ation			
12.1. Toxicity					
Information on compo	nent Eth	ane-1,2-diol			
Toxicity to	Value /	exposure time	Species		
fish		72860 mg/l / 96 h	Pimephales promelas (Fathead minnow)		
lenter's contestions		15380 mg/l / 7 d			
daphnia and other		>100 mg/l / 48 h	Daphnia magna (Water flea)		
aquatic invertebrates algae		8590 mg/l / 7 d 6500 - 13000 mg/l / 96 h	Ceriodaphnia dubia (Water flea) Pseudokirchneriella subcapitata (Green algae)		
12.2. Persistence and degradability: 12.3. Bioaccumulative		dation: 90-100 % (10 readiliy biodegradable	nent Ethane-1,2-diol: Biodegradability: Biodegra- d), method: OECD test guideline 301 A. Result: ent Ethane-1,2-diol: Bioaccumulation: Bioconcen-		
12.3. Bioaccumulative potential:		tration factor (BCF): 10. Partition coefficient n-octanol/H ₂ 0: log P_{ow} : -1.93			
12.4. Mobility in soil:		No data available.			
12.5-Results of PBT a vPvB assessment:	nd		ontain a substance fulfilling the PBT criteria (per- e/toxic) or the vPvB criteria (very persistent/very		
12.6. Other adverse ef	fects:	No data available.			
12.7. Further information	ion:	No further information.			
ECTION 13: Disposal	conside	rations			
13.1. Waste treatment	methods	;			
Product:		According to the Europ	nce with local regulations. Dean Waste Catalogue (EWC), waste codes are		
			ut application specific. Waste codes should be		

Contaminated packaging:Dispose of as the product. Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14: Transport information

	ADR/ RID	ADN	IMDG	IATA/ ICAO
	Not cla	ssified as a da transport r		d under
14.1. UN number	-	-	-	-
14.2. UN proper shipping name	-	-	-	-
14.3. Transport hazard classes	-	-	-	-
14.4. Packing group	-	-	-	-
14.5. Environmental hazards	-	-	-	-
14.6. Special precautions for user	-	-	-	-

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not evaluated.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance/mixture

Legal basis	Remark / Evaluation
Regulation (EC) No. 649/2012 of the European Parliament and the Council concerning the export and import	Not applicable
REACH - Candidate List of Substances of Very High Concern for Authorisa- tion (Article 59)	Not applicable
Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer	Not applicable
Regulation (EC) No. 850/2004 on persistent organic pollutants	Not applicable
Seveso III - Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances	Not applicable

Other regulations

Take note of Directive 94/33/EC on the protection of young people at work.

15.2. Chemical Safety Assessment

A Chemical Safety Assessment was not carried out for the product.

SECTION 16: Other information

I	Full text of the abbreviations of classifications and H-Statements used in sections 2 and 3		
	Acute Tox. 4	Acute Toxicity, Category 4.	
	STOT RE 2	Specific target organ toxiciy - repeated exposure, Category 2	
	H302	Harmful if swallowed	
	H373	May cause damage to kidneys through prolonged or repeated exposure	
	1070	by swallowing	
	Other abbreviations used in this safety data sheet in alphabetical order		
	ADN	European agreement concerning the international carriage of dangerous	
		goods by inland waterways	
	ADR	European agreement concerning the international carriage of dangerous	
		goods by road	
	ASTM	American Society for Testing and Materials	
	ATE	Acute Toxicity Estimate	
	CAS number	Chemical Abstracts Service number	
	CLP	Regulation (EC) No. 1272/2008 on classification, labeling and packaging	
		of chemical substances and mixtures	
	DIN	German Institute for Standardisation/German Industrial Standard	
	DNEL	Derived No Effect Level	
	EC50	Median Effective Concentration	
	EC number	EINECS number (European Inventory of Existing Substances) or ELINCS	
		number (European List of Notified Chemical Substances)	
	GB EH40	UK EH40 WEL-Workplace Exposure Limits	
	GB EH40 STEL		
		Short-term exposure limit (15-minute reference period)	
	GB EH40 TWA	Long-term exposure limit (8-hour TWA reference period)	
	IATA	International Air Transport Association	
	IBC	International Code for the Construction and Equipment of Ships carrying	
	1040	Dangerous Chemicals in Bulk	
	ICAO	International Civil Aviation Organization	
	IMDG	International Maritime Dangerous Goods Code	
	INDEX number	Identification code for hazardous substances, Annex VI of Regulation (EC)	
	100	No. 1272/2008	
	ISO	International Organisation for Standardisation/International Standard	
	LC50	Median Lethal Concentration	
	LD50	Median Lethal Dose	
	MARPOL	International Convention for the Prevention of Marine Pollution from Ships	
	NOAEL	No Observed Adverse Effect Level	
	NOEC	No Observed Effect Concentration	

Version: 3.3, ID-No.: 2100-g-01_GB-GB

SECTION 16: Other information - Continuation

OECD	Organisation for Economic Cooperation and Development	
PNEC	Predicted No Effect Concentration	
REACH	Regulation (EC) No. 1907/2006 on Registration, Evaluation, Authorisation and Restriction of Chemicals	
RID	Regulation concerning the international carriage of dangerous goods by rail	
2000/39/EC	European Commission Directive 2000/39/EC establishing a first list of indi- cative occupational exposure limit values	
2000/39/EC STEL	Short Term Exposure Limit	
2000/39/EC TWA	Time Weighted Average limit value - eight hours	
Further information		
Sources of key data used to compile the safety data sheet: Internal technical data, data from component		

SDS, OECD eChem Portal search results and European Chemicals Agency [ECHA].

Revision date:	01.08.2020
Date of previous version:	01.07.2019

Vertical lines in the left hand margin indicate an amendment from the previous version.

The information provided in this safety data sheet (SDS) is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific product identified at the top of this SDS and may not be valid when the SDS product is used in combination with any other materials or in any process, unless specified in the text. Product users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS product in the user's end product, if applicable.