SysMaster 150-8-6 WXOF A911000

Product specification sheet





Technical Data	A911000
Air displacement	150 l/min
Max. free air delivery	70 l/min
Max. pressure	6/8 bar
Cylinder/Stage	1/1
Tank capacity	51
Voltage	230 Volt/50 Hz
Motor output	1,1 kW
Drive	2450 min ⁻¹
Noise level	89 dB(A)
Dimensions (wxdxh)	296 x 396 x 316mm
Weight	13 kg

Product description

Fact Sheet

- Portable, direct driven and oil free piston compressor
- For applications up to 8 bar
- This high quality performing air compressor is for private as well as for professional use
- Equipped with pressure reducer and pressure gauges for measuring tank and outlet pressure
- Best protection of the damageable parts due to the protective Systainer® lid
- Applications: Using smaller sized staple and nail gun, blow out guns, cartridge guns, grease and rivet guns

SysMaster 150-8-6 WXOF A911000

Product specification sheet





on the top of the Systainer



Additional space separate compartment for plug power cable

High flexibility is provided by 4 m cable lenght

Systamatic working the Systainer connects compressor with air tools and accessories systematically

Great sturdiness Systainer protects the compressor unit. Thousands of sold systainers verify its high protection perfomance

due to the oil free aggregate

Best protection of the instruments thanks to functional and protective blind cover

Excellent working comfort due to integrated control panel with quick coupling, pressure reducer and two clearly arranged pressure gauges in operating height for measuring tank and outlet pressure

Very low-maintenance

Straightforward maintenance discharge port is centrally fitted

Long service life

thanks to the 10 years anticorrosion warranty on the compressed air tank

Further information

Operates fully automatically	With on/off switch
Scope of delivery	Instruction manual
Warranty	12 months for industrial use 24 months for private (non-commercial) use 36 months when registrated online