



Fulfill your customers' highest demands on the hygiene of drinking water and efficiency - with the horizontal OEG hygienic storage tanks!

The structure of these storage tanks is fundamentally different from usual, large-volume domestic water tanks. A built-in corrugated stainless steel pipe separates the drinking water from the heating water and serves as a powerful heat exchanger at the same time. Thus, the advantages of a buffer tank are combined with those of a flow heater.

The drinking water flows through the corrugated stainless steel pipe in the water of the heated tank only if required. This leads to a very low energy consumption and you can guarantee your customers legionella-free drinking water. You will not need a legionella protection programme in the regulation.

At all times, consumers are provided with hygienically clean, fresh water at their desired temperature.

The horizontal arrangement of the hygienic storage tanks makes them ideal for the use in places unsuitable for vertical (standing) storage tanks (e.g. below inclined walls and stairs). That is the reason why your customers can benefit from the advantages of a hygienic tank even when space is limited.

Just compare! Due to the horizontal arrangement of the heat exchangers in the horizontal OEG hygienic storage tanks, you can offer your customers benefits compared to other products in the market. Only by the horizontal installation of the heat exchangers, an efficient heat stratification is achieved. The generously dimensioned heat exchanger surfaces provide for another energetic advantage over other products available in the market.

Indicazioni conformi al regolamento UE 812/2013

Nome o marchio del fornitore:	OEG GmbH
Identificatore modello del fornitore:	516006324 - Accumulatore acqua fresca orizzontale 120 litri
Classe di efficienza energetica del modello:	A+
Perdite termiche in watt:	26
Volume di stoccaggio in litri:	117

Generale

OEG Nr.:	516006324
Capacità nominale a norma EN 12897:	120
Isolamento secondo la DIN 4102-1 con classe di protezione antincendio B2:	solid foamed insulation
Peso [kg]:	55
Altezza totale con isolamento [mm]:	700
Larghezza [cm]Larghezza [mm]:	610
Lunghezza [mm]Lunghezza [cm]:	785

Pure+ Accumulatore acqua fresca orizzontale

120 litri



Energia

Classe di efficienza energetica conforme al regolamento UE numero 812/2013:	A+
Perdita termica secondo EN 12897 [W]:	26
Perdite di calore in stand-by secondo la norma EN 12897 [kWh/24h]:	0,624
Portata (45 °) [l]:	55
Coefficiente di resa termica a norma DIN 4708:	0,80

Serbatoio

Volume effettivo conforme alla norma EN 12897 [l]:	117
p _{max} Serbatoio [bar]:	3
t _{max} Serbatoio [°C]:	95
t _{min} Serbatoio [°C]:	20

Scambiatore di calore per acqua potabile

p _{max} Scambiatore di calore per acqua potabile [bar]:	6
t _{max} Scambiatore di calore per acqua potabile [°C]:	95

Raccordi

Provvedimento di raccordi:	front/rear
Raccordo sonda [Ø mm / morsetto]:	6 mm
Raccordo generatore di calore [filettatura]:	R 1"
Raccordo resistenza elettrica [filettatura]:	Rp 1 1/2"
Riscaldatore a vite con profondità massima a immersione [mm]:	500