

No. 1907/2006 (REACH) Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.5

Flex 310 M Stainless-Steel

! SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product Flex 310 M Stainless-Steel

Code-Nr. 136560

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended intended purpose(s)

1-Component Adhesives and Sealants, permanently elastic

1.3. Details of the supplier of the safety data sheet

Distributor WEICON GmbH & Co. KG

Königsberger Str. 255,, DE-48157 Münster

Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322 - 244

E-Mail: msds@weicon.de Internet: www.weicon.de

Advice Produktsicherheit / Product-Safety-Department

> Phone ++49(0)251 / 9322 - 0 E-mail (competent person):

msds@weicon.de

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:

++44 1865 407333 (English)

TRANSPORT EMERGENCY CONTACT - UK, UAE, South

Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):

Tel: ++49 69 222 25285 (Deutsch, Englisch)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

This mixture is not classified as hazardous according to Regulation (EC) 1272/2008 [GHS].

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]

Special rules for supplemental label elements for certain mixtures

Contains Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, 3-(2-Aminoethylamino)-propyltrimethoxysilan, N-[3-(dimethoxymethylsilyl)propyl]ethylenediamine, dioctyltinbis(acetylacetonate). May produce an allergic reaction.

2.3. Other hazards



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.5

Flex 310 M Stainless-Steel

Information pertaining to special dangers for human and environment

Although this product is not subject to reporting requirements for hazardous products, we recommend compliance with the safety recommendations.

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.1. Substances

not applicable

3.2. Mixtures

Description

Sealant

Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
2768-02-7	220-449-8	trimethoxyvinylsilane	1 < 5	Flam. Liq. 3, H226 / Acute Tox. 4;, H332
REACH				
CAS No	Name			REACH registration number
2768-02-7	trimethoxyvinylsilane 01-2119513215-52-xxxx		01-2119513215-52-xxxx	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove moisted clothing immediately.

In case of inhalation

Ensure of fresh air.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off immediately with plenty of water.

In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

In case of ingestion

Do not induce vomiting.

If swallowed by mistake drink plenty of water and seek medical treatment.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Product does not burn, fire-extinguishing activities according to surrounding.



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.5

Flex 310 M Stainless-Steel

5.2. Special hazards arising from the substance or mixture

In case of fire formation of dangerous gases possible.

Carbon monoxide (CO)

Carbon dioxide (CO2)

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

Additional information

Cool endangered containers with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Ensure adequate ventilation.

Use personal protective clothing.

Use breathing apparatus if exposed to vapours/dust/aerosol.

6.2. Environmental precautions

Do not discharge into the drains or bodies of water..

6.3. Methods and material for containment and cleaning up

Take up mechanically and send for disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8 Emergency telephone number: see section 1

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

General protective measures

Do not inhale vapours.

Avoid contact with eyes and skin

Hygiene measures

Keep away from food and drink.

Wash hands before breaks and after work.

Advice on protection against fire and explosion

Pay attention to general rules of internal fire prevention.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep only in original container.

Advice on storage compatibility

Do not store together with animal feedstuffs.

Do not store together with food.



Remark

No. 1907/2006 (REACH) Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.5

Flex 310 M Stainless-Steel

Further information on storage conditions

Protect from frost.

Protect from heat and direct solar radiation.

Store container at cool and aired place.

Store in a dry place.

7.3. Specific end use(s)

Recommendation(s) for intended use

See section 1.2

SECTION 8: Exposure controls/personal protection

Substance name

8.1. Control parameters

DNEL-/PNEC-values

CAS No

2768-02-7	trimethoxyvinylsilane	4,9 mg/m3	DNEL long-term inhalative (systemic)	
		0,69 mg/kg bw/day	DNEL long-term dermal (systemic)	
DNEL Cons	umer			
CAS No	Substance name	Value	Code	Remark
2768-02-7	trimethoxyvinylsilane	93,4 mg/m3	DNEL acute inhalative (systemic)	
		26,9 mg/kg bw/day	DNEL acute dermal, short-term (systemic)	
		1,04 mg/m3	DNEL long-term inhalative (systemic)	
		0,3 mg/kg bw/day	DNEL acute dermal, short-term (systemic)	
PNEC				
CAS No	Substance name	Value	Code	Remark
2768-02-7	trimethoxyvinylsilane	0,034 mg/l	PNEC aquatic, marine water	
		0,34 mg/l	PNEC aquatic, freshwater	
		1,24 mg/kg dw	PNEC sediment, freshwater	
		0,12 mg/kg dw	PNEC sediment, marine water	
		3,4 mg/l	PNEC aquatic, intermittent release	

Code

Value

Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls Respiratory protection

Not required

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: butyl rubber, 0,7mm; 480min



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.5

Flex 310 M Stainless-Steel

Eye protection

tightly fitting goggles

Other protection measures

protective clothing

Appropriate engineering controls

Sufficient ventilation and exhaustion.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

AppearanceColourOdourpastygreycharacteristic

Odour threshold not determined

temperature

Important health, safety and environmental information

Method Value Temperature at Remark pH value not determined 270 °C boiling point melting point not determined > 100 °C Flash point not determined Vapourisation rate Flammable (solid) not applicable not applicable Flammability (gas) 420 °C Ignition temperature Self ignition temperature no 0,1 Vol-% Lower explosion limit **Upper explosion limit** 0,2 Vol-% not determined Vapour pressure 20 °C 1,06 g/cm3 Relative density Vapour density not determined Solubility in water No or low immiscibility Solubility/other not determined not determined Partition coefficient noctanol/water (log P O/W) not determined Decomposition



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.5

Flex 310 M Stainless-Steel

Method Value Temperature Remark at not determined Viscosity dynamic not determined Viscosity kinematic Solvent content 3,43 % **Oxidising properties** No information available. **Explosive properties** 9.2. Other information No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No information available.

10.3. Possibility of hazardous reactions

No dangerous reactions known.

10.4. Conditions to avoid

Keep away from heat.

10.5. Incompatible materials

Substances to avoid

No dangerous reactions known.

10.6. Hazardous decomposition products

Carbon monoxide
Carbon dioxide

Thermal decomposition

Remark No decomposition if used as directed.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark
Skin irritation	non-irritant			
Eye irritation	non-irritant			
Ckin consitization	non-sensitizing			



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.5

Flex 310 M Stainless-Steel

Subacute Toxicity - Carcinogenicity

	Value	Species	Method	Validation
Chronic Toxicity				-
Mutagenicity				No experimental information on genotoxicity in vitro available.
Reproduction- Toxicity				No indications of toxic effects were observed in reproduction studies in animals.
Carcinogenicity				No indications of carcinogenic effects are available from long-term trials.

Experiences made from practice

According to our experience and current information, the product has no detrimental effects on health if handled and used correctly

Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

The product has not been tested. The information is derived from the properties of the individual components.

SECTION 12: Ecological information

12.1. Toxicity

No information available.

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

The product has not been tested. Because of the product's consistency and low solubility in water bioavailability is not likely.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

General regulation

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment.

The ecotoxic effect of the product has not been tested. The information on this is given on the basis of details in the literature.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste code No.

Name of waste

08 04 09*

waste adhesives and sealants containing organic solvents or other hazardous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.5

Flex 310 M Stainless-Steel

Recommendations for the product

Remove in accordance with local official regulations.

Recommendations for packaging

Dispose of according to the local waste regulations.

General information

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	-	-	-
14.2. UN proper shipping name	-	-	-
14.3. Transport hazard class(es)	-	-	-
14.4. Packing group	-	-	-
14.5. Environmental hazard	s -	-	-

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

Transport/further information

No dangerous goods as defined by the transport regulations - ADR/RID, IMDG, ICAO/IATA-DGR.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC standard

VOC content 3,43 % **VOC value** 36,4 g/L

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EUdirectives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.4



No. 1907/2006 (REACH) Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.5

Flex 310 M Stainless-Steel

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.