

# Stapler KLG 80-16

## D200091

### Product specification sheet



Technical Data	D200091
Trip mechanism	single shot
Air consumption per shot	0,3 l per shot
Type of staplers	Type 80
Stapler length	4-16 mm
Stapler crown width	12,8 mm
Stapler wire diameter	0,7 x 0,9 mm
Magazine capacity (number of staplers)	157
Operating pressure	4-7 bar
Vibration value	1,85 m/s <sup>2</sup>
Sound pressure level (LPA)	84 dB (A)
Sound power level (LWA)	97 dB (A)
Dimensions (WxDxH)	237x43x153
Weight	0,87 kg

## Product description

### Fact Sheet

- Users: carpenters, interior designers, upholsterers
- Perfect for mounting of films, tissues, leather, insulating materials, carpets, panelling
- Extra light and handy housing
- Two stage trigger prevents accidental firing of staples
- Bottom loading magazine allows quick and easy reloading
- Can be used in difficult to access locations

# Stapler KLG 80-16

## D200091

### Product specification sheet



**Rubber grip**  
absorbs shock  
and vibration and  
insulates against  
cold

**Two stage safety  
trigger** avoids  
unintentional firing

**Direction of  
exhaust air away  
from the  
operator** which  
minimizes  
contamination of  
the work piece and  
noise

**Easy troubleshooting**  
due to functional  
magazine rack with  
easy access to remove  
any blockages and  
obstructions

**Bottom loading  
magazine** for fast  
reloading

**Long nose** for  
using in difficult to  
access locations



**Lighter and  
compact stapler**  
which is less tiring  
to use if a large  
amount of stapling  
is required

### Further information

#### Scope of delivery

Delivered in cardboard box with lubricant oil, hex wrench and instruction manual

#### Warranty

36 months when registered online  
24 months for private (non-commercial) use  
12 months for industrial use